

# PORTABLE HANDLIGHTS: DRY BATTERY

PRODUCT  
CODE

C

These lights were designed with one very important feature in mind. The head can swivel up and down while the battery stays level with the ground. For utility company pole inspectors, this allows them to walk long distances without arm fatigue. Also it has spot lamp on one side and flood on the other. This provides greater illumination than units that have two filaments in a single lamp.

(A) **MODEL: A-45-DRD** - Spotlight on one side, flashing red/amber the other. Can use either or both at the same time.

**MODEL: A-45-D** - Spotlight on one side, flood on the other. Can use either not both at same time

**MODEL: A-45-DR** - Floodlight on one side, flashing warning the other. Use either.

(B) **MODEL: A55-4013** - As shown with solid colored head and flood pattern sealed beam lamp. Battery life: Flood - 900 CP, 6-8 hours.

**MODEL: A55-4013-AMBER** - With see through amber head for extra safety. Flood light pattern for working. Battery life: Flood - 900 CP, 6-8 hours.

**MODEL: A55-4017-AMBER** - Single direction with a dual filament lamp providing both flood or spot pattern. Battery life: Spot - 16,000 CP, 16 hours. Flood - 3,000 CP, 32 hours.

\* All of our lanterns use sealed beam lamps which gives the end user the ability to change intensity or patterns by simply using another lamp. Or the light can be ordered with a different lamp. Uses 7 1/2 volt dry cell battery. Eveready 715 or NEDA 903.

(C) **MODEL: FLASHLT-CONE** - This flashlight has a brilliant white beam - dazzling red flare which is visible for a 1/2 mile. Used in areas of traffic control, and as a car safety light. Compact safety flare snaps off easily for storage.

(D) **MODEL: FLASHLT-2D** - Made of high intensity polyethylene. Has a large on/off slide switch and has a closed end so it fits easily into a pocket. Uses 2 standard "D" batteries.

A)



A45-D

B)



A55

C)

FLASHLT-CONE



D)

FLASHLT-2D



JULIAN A. McDERMOTT CORPORATION

1639 STEPHEN ST., RIDGEWOOD, NY 11385 TEL (800) 842-5708 FAX (718) 381-0229